

Controller

NetBee



Your distributor

Premium Power Tools



MADE IN GERMANY



HS-Technik GmbH
High - System - Technik

NetBee-Series

Controller for battery tightening and riveting tools

- **Up to 12 HST Tools**
(TorqBee / RivBee / NutBee)
- **Electronic Torque Wrench**
(SCS Freedom 4)
- **Max. two work stations**
- **7" Color-Touch-Display**
- **Webinterface for programming and visualization**
- **Interfaces**
 - 2 x Ethernet
 - 1 x USB-C
 - 4 x USB
 - 4 outputs (NetBee-4O-*)
 - 16 inputs / 16 outputs (NetBee-16IO-*)
- **Can be connected to:**
 - OpenProtocol
 - PFCS
 - ToolsNet
 - IPM
 - VW XML (not approved yet)
 - Fieldbus
- **Accessories**
 - Barcode reader
 - Printer
 - Label printer
 - Socket tray
- **Memory**
 - 100.000 results
 - 100.000 curves
- **Upgrade to max. 6 stations and Multibrand function possible**

No Wi-Fi Access Point incl.



| Order no. | Description |
|---------------|---------------------------------------|
| NetBee-4O-* | NetBee Controller with 4 outputs |
| NetBee-16IO-* | NetBee Controller with 16 in-/outputs |

| Technical data | NetBee-xxxO-* |
|-----------------------|-------------------------|
| Dimensions L x W x H | 208 x 319 x 199 mm |
| Weight | 5.30 kg |
| Operating temperature | 5 - 40 °Celsius |
| Humidity | 95 %, not condensing |
| Protection category | IP40 |
| Voltage supply | 100 - 240 VAC, 50/60 Hz |

| Order no. | Description |
|-----------|--|
| NetBee-UH | Upgrade to max. 6 stations and Multibrand function |

*
 EU = Schuko plug
 US = USA plug
 UK = UK plug
 AU = Australia plug

NetBee-Series

Socket tray



| Order-no. | Description | |
|-----------------|--|--------------------------------------|
| NetBee-ST6-39 | 6-bay socket tray for NetBee, max. socket diameter 39 mm | Supplied without CAN and power cable |
| NetBee-ST6-50 | 6-bay socket tray for NetBee, max. socket diameter 50 mm | Supplied without CAN and power cable |
| NetBee-ST8-39 | 8-bay socket tray for NetBee, max. socket diameter 39 mm | Supplied without CAN and power cable |
| NetBee-ST6-39-W | 6-bay Wi-Fi socket tray for NetBee, max. socket diameter 39 mm | Supplied without battery |
| NetBee-ST6-50-W | 6-bay Wi-Fi socket tray for NetBee, max. socket diameter 50 mm | Supplied without battery |
| NetBee-ST8-39-W | 8-bay Wi-Fi socket tray for NetBee, max. socket diameter 39 mm | Supplied without battery |

| Technical data | NetBee-ST6-39(-W) | NetBee-ST6-50(-W) | NetBee-ST8-39(-W) |
|-----------------------|-------------------------|-------------------------|-------------------------|
| Dimensions L × W × H | 302 × 149 × 160 mm | 302 × 149 × 160 mm | 402 × 149 × 160 mm |
| Weight | 4.00 kg | 4.00 kg | 5.20 kg |
| Operating temperature | 5 - 40 °Celsius | 5 - 40 °Celsius | 5 - 40 °Celsius |
| Humidity | 95 %, not condensing | 95 %, not condensing | 95 %, not condensing |
| Protection category | IP40 | IP40 | IP40 |
| Voltage supply | +24 VDC, maximum 800 mA | +24 VDC, maximum 800 mA | +24 VDC, maximum 800 mA |



HS-Technik GmbH
High - System - Technik

Im Martelacker 12

D-79588 Efringen-Kirchen

Telephone: +49 (0) 76 28 - 91 11-0

Fax: +49 (0) 76 28 - 91 11-90

E-mail: info@hs-technik.com

Internet: www.hs-technik.com

© Copyright October 2021

Subject to modifications and errors. All figures are non-binding.

We reserve the right to make technical changes to our products and the range of products as a result of further development.

Reproduction and the use of texts, even excerpts of our brochures is prohibited and will be prosecuted.