

# Blind rivet nut tool

NutBee® LF-Series



Premium Power Tools



MADE IN GERMANY



**HS-Technik** GmbH  
High - System - Technik

# NutBee® LF-Series

## Force controlled battery blind rivet nut and blind rivet bolt tool

- Force-controlled setting process
- Force sensor, precision class  $\leq 0.5\%$
- Controlling the setting speed based on the force
- Machine capability  
+/- 7 % Cm  $\geq 2.00$  / Cmk  $\geq 1.67$
- Adjusting the setting force using buttons on the display
- Quick-change nose piece from M3 - M10\*
- OK/NOK Evaluation of a force tolerance of +/- 10 % of the nominal value
- Display of the riveting results on OLED-Display (green/red smiley face)
- Handle vibration alarm
- Multi-color LED status indicator
- Intelligent battery management
- Brushless high-power motor
- LED to illuminate the setting area
- Recuperation extends the battery service time
- Updates can be installed via USB



\* up to 25 kN

## Technical data

Model	max. setting force	max. setting stroke	Dimensions L x W x H	Weight
NBLF-25	25 kN (5620 lbf)	21 mm (0.83 in)	212 x 73 x 270 mm (8.35 x 2.87 x 10.63 in)	2.00 kg (4.41 lbs)

Delivered without nose piece and threaded mandrel.  
Dimensions and weight indications without battery.  
At usage above 20 kN limited warranty.

For more  
information about  
other NutBee models,  
tool structure and  
accessories click  
here!



# **HS-Technik GmbH**

**High - System - Technik**

Im Martelacker 12  
D-79588 Efringen-Kirchen  
Phone: +49 (0) 76 28 - 91 11-0  
Fax: +49 (0) 76 28 - 91 11-90  
E-mail: [info@hs-technik.com](mailto:info@hs-technik.com)  
Internet: [www.hs-technik.com](http://www.hs-technik.com)

© Copyright June 2021

Subject to modifications and errors. All figures are non-binding.

We reserve the right to make technical changes to our products and the range of products as a result of further development.  
Reproduction and the use of texts, even excerpts of our brochures is prohibited and will be prosecuted.