



## CL series

No. 1 for use in modern precision production lines



- Brush driven motor
- Precise, stepless adjustment of the torque
- Quiet and low-vibration
- Low reaction moment, constant speed
- Easy changing of the blades

- ESD-EGB model available
- Optional pistol handle available for CL-6500NLX and CL-7000NLX
- ISO 5393 /VDI/VDE 2647 certified (proof of machine capability)

### Technical Data

Order no.	CL-2000	CL-3000	CL-4000*	CL-6500*	CL-7000
Torque range Nm	0,02 - 0,2	0,03 - 0,2	0,10 - 0,55	0,3 - 1,6	0,3 - 2,5
Power supplies	CLT-45-EU-HK / CLT-60-EU-HK				CLT-60-EU-HK
Speed 30 V rpm	680	1.000	1.000	900	750
Speed 20 V rpm	490	690	690	600	500
Handle diameter	26 mm	32,5 mm	32,5 mm	37 mm	37 mm
Length	166 mm	183 mm	197 mm	235 mm	255 mm
Adapter	HIOS H4	HIOS H4	HIOS H4, 1/4" Hex.	HIOS H5, 1/4" Hex.	HIOS H5, 1/4" Hex.
Weight	200 g	390 g	430 g	660 g	750 g

\*also available as push start (-PS)